

## **HEGS5BLX**

www.honeywellvideo.com

#### VIDEOBLOX KEYBOARD

The HEGS5BLX is a joystick keyboard controller for the Honeywell VideoBloX family of video matrix switching and control equipment. Most common functions required in controlling a small to medium sized VideoBloX systems can be readily accomplished using this compact keyboard.

The major functions integrated into the unit are complete control of the video matrix switching equipment, pan/tilt/zoom dome cameras (PTZs), and controlling the operation of sequences and the monitoring of alarms.

Manufactured of durable extruded aluminum with rugged positive action keys, the HEGS5BLX is designed for years of use. A high brightness, 2-line backlit LCD display makes operation and setup simple and straightforward.

#### **Market Opportunities**

The HEGS5BLX is the ideal keyboard controller for small to mid-sized VideoBloX installations. The keyboard's simple method of operation, low profile and durability make it the choice of security and surveillance professionals worldwide.

#### **Features**

- Rugged metal construction
- Positive action keys
- High brightness, 2-line backlit LCD display
- Major functions include: Input/output switching

- PTZ control
- VideoBloX Matrix control
- Activation of sequences and alarm acknowledgement




# **HEGS5BLX**

## **SPECIFICATIONS**

Operational	
Communication Speeds	RS232 - 1200 baud; HVB232422 converter must be used when using HEGS5BLX with VideoBloX RS485 - not used
Operating Distances	RS232 - 50' (12.7m) maximum
LCD Touch Screen	2-line, backlit
Joystick	3-axis proportional control
Keypad	Durable, hard rubber keys
PTZ Dome Control	Full PTZ control using joystick; keypad control of iris open/close/auto and focus far/near/out
Multiplexer Control	Remote control of up to 16 multiplexers
VCR Control	Remote control of up to 16 VCRs
Electrical	
Input Voltage	100 - 240 VAC
Operating Voltage	12 VDC
Power Consumption	6 W
Power Consumption  Mechanical	6 W
<u>'</u>	13" x 3.75" x 6.875" (330 mm x 95 mm x 175 mm)
Mechanical Dimensions	13" × 3.75" × 6.875"
Mechanical Dimensions (W x H x D)	13" x 3.75" x 6.875" (330 mm x 95 mm x 175 mm) Unit: 3 lbs (1.36 kg)
Mechanical Dimensions (W x H x D) Weight	13" x 3.75" x 6.875" (330 mm x 95 mm x 175 mm) Unit: 3 lbs (1.36 kg) Shipping:6 lbs (2.72 kg) Housing: Extruded aluminum
Mechanical Dimensions (W x H x D) Weight Construction	13" x 3.75" x 6.875" (330 mm x 95 mm x 175 mm) Unit: 3 lbs (1.36 kg) Shipping:6 lbs (2.72 kg) Housing: Extruded aluminum
Mechanical Dimensions (W x H x D) Weight Construction Connections	13" x 3.75" x 6.875" (330 mm x 95 mm x 175 mm) Unit: 3 lbs (1.36 kg) Shipping:6 lbs (2.72 kg) Housing: Extruded aluminum Finish: Light gray powder coating  RJ12 connector with 1x RS485

Environmental	
Temperature	Operating: 32°F - 122°F (0°C - 50°C) Storage: 14° - 140°F (-10° - 60°C)
Relative Humidity	0% - 95% (non-condensing)
Regulatory	
Emissions	FCC Part 15, Class A CIS PR22:1994
Immunity	IEC 61000-4-2:1995 IEC 61000-4-3:1996 IEC 61000-4-4:1995 IEC 61000-4-6:2005
Accessories	
HVB232422	RS232 to RS422 converter (required)
System Compatibility	/
Systems	VideoBloX VideoBloX Lite



Ordering	
HEGS5BLX	VideoBloX joystick keyboard (keyboard only)
HEGS5BLXKT	Kit, HEGS5BLX VideoBloX joystick keyboard and HVB232422 RS232 to RS422 converter

**NOTE:** Honeywell reserves the right, without notification, to make changes in product design or specifications.

### **Honeywell Security**

Honeywell Video Systems 2700 Blankenbaker Pkwy, Suite 150 Louisville, KY 40299 1.800.796.CCTV

www.honeywell.com © 2008 Honeywell International Inc.



