

CAMERAS

Honeywell's Performance Series offers competitively-priced cameras for everyday security applications from a partner you know and trust.
Performance you want at the price you need.

Quick Reference Guide: Performance Series

	Part Number	Description	Lens	Horizontal Resolution	Input Voltage	Minimum Illumination	IR Illumination	IP Rating	Recommended Accessories
Indoor Minidomes									
	HD40P	Standard Res.	Fixed Lens (f=3.8 mm)	420 TVL	12 VDC	0.1 lux (Color)	N/A	N/A	Power Supply: HPT12DC500 Wall Mount Bracket: HDPR-WK2
	HD41	Super High Res. Day/Night	VFAI Lens (f=2.8-12 mm)	620 TVL	12 VDC	0.3 lux (Color)	N/A	N/A	Power Supply: HPT12DC500
IR Indoor Minidomes									
	HD60	Standard Res. Day/Night	Fixed Lens (f=4.0 mm)	380 TVL	12 VDC	Day (0.1 lux), Night (0.00 lux)	24 IR LED 50 ft., 15 m	N/A	Power Supply: HPT12DC500
	HD61	Standard Res. Day/Night	Manual Vari-focal Lens (f=4-9 mm)	380 TVL	12 VDC	Day (0.3 lux), Night (0.00 lux)	20 IR LED 65 ft., 20 m	N/A	Power Supply: HPT12DC500
	HD62	High Res. Day/Night	Manual Vari-focal Lens (f=2.8-12 mm)	630 TVL	12 VDC	Day (0.1 lux), Night (0.00 lux)	20 IR LED 65 ft., 20 m	N/A	Power Supply: HPT12DC500
IR Indoor/Outdoor Rugged Ball Cameras									
	HD30	Standard Res. Day/Night	Fixed Lens (f=3.6 mm)	420 TVL	12 VDC	0.0 lux (IR LEDs ON)	21 LED 20 ft., 6 m	IP66	Power Supply: HPT12DC500
	HD31 HD31W	Super High Res. Day/Night, DNR	VFAI Lens (f=2.8-12 mm)	620 TVL	12 VDC	0.0 lux (IR LEDs ON)	35 LED 65 ft., 20 m	IP66	Power Supply: HPT12DC500
IR Indoor/Outdoor Rugged Minidomes									
	HD70P	High Res. Day/Night, DNR	Fixed Lens (f=3.8 mm)	600 TVL	12 VDC	Day (0.3 lux), Night (0.00 lux)	Smart IR 20 IR LED 50 ft., 15 m	IP66	Power Supply: HPT12DC500 Wall Mount Bracket: HDPR-WK Pendant Mount Bracket: HDPR-PK
	HD73P	High Res. True Day/Night, DNR	VFAI Lens (f=3.8-9.5 mm)	600 TVL	12 VDC	Day (0.3 lux), Night (0.00 lux)	Smart IR 20 IR LED 65 ft., 20 m	IP66	Power Supply: HPT12DC500 Wall Mount Bracket: HDPR-WK Pendant Mount Bracket: HDPR-PK
Indoor/Outdoor Rugged Minidomes									
	HD50P	High Res. Color, DNR	Fixed Lens (f=3.8 mm)	600 TVL	12 VDC	0.9 lux	N/A	IP66	Power Supply: HPT12DC500 Wall Mount Bracket: HDPR-WK Pendant Mount Bracket: HDPR-PK
	HD51P	High Res. Color, DNR	VFAI Lens (f=3.8-9.5 mm)	600 TVL	12 VDC	0.3 lux	N/A	IP66	Power Supply: HPT12DC500 Wall Mount Bracket: HDPR-WK Pendant Mount Bracket: HDPR-PK
IR Indoor/Outdoor Bullet Cameras									
	HB74	Standard Res. Day/Night	Fixed Lens (f=3.8 mm)	420 TVL	12 VDC	0.0 lux (IR LEDs on)	Smart IR 12 LED 45 ft., 14 m	IP66	Power Supply: HPT12DC500
	HB75	High Res. True Day/Night, DNR	VFAI Lens (f=3.8-9.5 mm)	600 TVL	12 VDC	0.0 lux (IR LEDs on)	Smart IR 18 LED 65 ft., 20 m	IP66	Power Supply: HPT12DC500

Quick Reference Guide: Performance Series PLUS

	Part Number	Description	Lens	Horizontal Resolution	Input Voltage	Minimum Illumination	IR Illumination	IP Rating	Recommended Accessories
IR Indoor Minidome Camera									
	HD262	Super High Res. Day/Night, DNR	VFAI Lens (f=2.8-12 mm)	620 TVL	12 VDC/ 24 VAC	0.0 lux (IR LEDs ON)	Smart IR 28 LED, 65 ft., 20 m	N/A	Power Supply: HPT12DC500, HPT2440 Wall Mount Bracket: HDPR-WK2
IR Indoor/Outdoor Bullet Camera									
	HB273	Super High Res. Day/Night, DNR	VFAI Lens (f=9-22 mm)	620 TVL	12 VDC/ 20 VAC	0.0 lux (IR LEDs ON)	Smart IR 42 LED 100 ft., 30 m	IP66	Power Supply: HPT12DC500, HPT2440
Indoor/Outdoor Rugged Minidome									
	HD251	Super High Res. Day/Night, DNR	VFAI Lens (f=2.8-12 mm)	620 TVL	12 VDC/ 24 VAC	0.3 lux (Color)	N/A	IP66	Power Supply: HPT12DC500, HPT2440 Wall Mount Bracket: HDPR-WK1
IR Indoor/Outdoor Rugged Minidome									
	HD273	High Res. True Day/Night, DNR	VFAI Lens (f=3.8-9.5 mm)	600 TVL	12 VDC/ 24 VAC	0.0 lux (IR LEDs ON)	Smart IR 20 LED 65 ft., 20 m	IP66	Power Supply: HPT12DC500, HPT2440 Wall Mount Bracket: HDPR-WK



Performance Series

The Performance Series lineup of feature-rich cameras and DVRs provide affordable video surveillance solutions to meet a wide range of everyday security applications. All analog Performance Series products are backed by Honeywell's three-year warranty and the 365 Swap for easy, no-hassle returns and exchanges on defective product for 365 days after purchase.


DVRS

Our digital video recorders support a wide variety of user-friendly capabilities such as mouse operation, IR remote control, remote connectivity and best-in-class search engines.

960H camera support

Quick Reference Guide: Performance Series DVRs

Part Number	Channels	Storage	IPS Recorded	Removable Media
HRGX45	4	500 GB	120 ips 4CIF	2 USB ports
HRGX41	4	1 TB		
HRGX85	8	500 GB	240 ips 4CIF	2 USB ports
HRGX81	8	1 TB		
HRGX161	16	1 TB	480 ips 4CIF	2 USB ports
HRGX162	16	2 TB	480 ips 4CIF	2 USB ports




Audio Channels:
4 Line Input/1 Line Output

Monitor Outputs:
Main: HDMI, VGA and BNC
Spot: BNC

Remote Users:
– 24 simultaneous video streams
– Configurable user permissions
– Multi-site software, unlimited free licenses

Alarm Inputs/Outputs:
Inputs: 4/8/16
Outputs: 1/4/4

Compression: H.264



Free Mobile App:
Available for iPhone® and Android™

iPhone is a trademarks of Apple® Inc. All other trademarks are the property of their respective owners.

For more information: www.honeywellvideo.com

Automation and Control Solutions
Honeywell Security Products Americas
2700 Blankenbaker Pkwy, Suite 150
Louisville, KY 40299
1.800.323.4576
www.honeywell.com

L/HRGEXPEUF/D
June 2014
© 2014 Honeywell International Inc.

